



STORMY

Inflatable PFD Technologies

Australian Standard - **AS 4758**
International Standard - **ISO 12402-2**
Safety Deck Harness – **ISO 12401**
Spray Hood – **ISO 12402-8**
275 Newtons of Buoyancy
All PFD's (Lifejackets) are **WATER ACTIVATED**

ISO 275N SUPER PRO YOKE

Product Code: **ISYH-300**

- ✓ **Water Activation System** (will activate Automatically in an overboard emergency.)
- ✓ **Blanking cap** (supplied to change inflation to **Manual operation** –for Pull cord action)
- ✓ **60gm 1/2"CO² gas Cylinder** (offers **300N**)
- ✓ **Colour: Red**
- ✓ **Size range: Chest 55cm to 175cm & 40kg +**
- ✓ **Suitable to wear with heavy wet weather gear and for wearers 120kg+**
- ✓ **Lifting loop**
- ✓ **Leg strap with quick release buckle**
- ✓ **Padded fleece collar** (removable)
- ✓ **3M retro reflective tape**
- ✓ **Velcro closure cover**
- ✓ **Cape backstrap** (for greater comfort)
- ✓ **ISO 12401 Deck Safety Harness**
- ✓ **'D' ring for line attachment**
- ✓ **SOLAS Approved Lifejacket Light**
- ✓ **Built in easy don Spray hood ISO12402-8**



OPTIONAL EXTRAS

- EN 3 clip tether
- Extra recharge kit
- Dry Bag



33 Electra Place,
Mornington 7018
Tasmania Australia
Ph: 03 6245 0443
Fax: 03 6245 0446
www.stormylifejackets.com

